



**UNIVERSITI PUTRA MALAYSIA**

**THE EFFECTS OF ANGULARITY NUMBER ON  
TEXTURE DEPTHS AND SKID RESISTANCE  
OF STONE MASTIC ASPHALT**

**MOHTADY ALI MUSA**

**FK 2002 20**

**THE EFFECTS OF ANGULARITY NUMBER ON  
TEXTURE DEPTHS AND SKID RESISTANCE  
OF STONE MASTIC ASPHALT**

**By**

**MOHTADY ALI MUSA**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,  
in Fulfilment of the Requirements for the Degree of Master of Science**

**March 2002**



*Dedicated to my beloved family:*

*Father, may Allah send his mercy on his grave,*

*Mother, Brothers, Brother-in-law, and Sisters*

Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfilment of the requirement for the degree of Master of Science

**THE EFFECTS OF ANGULARITY NUMBER ON TEXTURE DEPTHS AND  
SKID RESISTANCE OF STONE MASTIC ASPHALT**

By

**MOHTADY ALI MUSA NORELDIEN**

**March 2002**

**Chairman : Professor Ir. Dr. Radin Umar Radin Sohadi**

**Faculty : Engineering**

Skidding of vehicles due to the lack of friction between pavement and tires, especially on wet pavements, is a problem to road users. There are many parameters that can help in attaining higher friction of pavement to control skidding such as microtexture and macrotexture of stones. One of the controlling parameters for macrotexture is the shape of stones for pavement construction. This research examines the angularity and related characteristics of aggregates for the formulation of high friction stone mastic asphalt wearing course.

In this study, only a small range of aggregate angularities could be produced using a UPM crushing machine. Hence, attempts to produce a wider range of angularities were aborted. Out of eighty one quarries investigated, only eight quarries were found suitable for this study. This is because of their different crushing systems which produce a wide range of angularities.

The collected aggregate materials were analysed for their Angularity Number and the Particle Shape Index as well as the other physical properties including petrography study. These aggregate materials were then mixed with the optimum content of 60-70 penetration grade asphalt cement as determined by the UPM in-house method of mix design. A total of one hundred and twenty samples were then casted. These samples were examined for their density, resilient modulus, and voids. The performance tests namely, Marshal stability, flow, static and dynamic creep modulus, and indirect tensile strength test were carried out. Regression analysis was done to correlate the aggregate Angularity Number with the stability, resilient modulus, density, Voids in Total Mix (VTM), Voids in Mineral Aggregate (VMA), static recovery efficiency and Surface Area (SA) using Microsoft EXCEL. The correlation was determined according to the value of the coefficient of regression. The result of the regression showed that there is a significant correlation of the density, VTM, VMA and SA with the Angularity Number.

Slab samples of size 0.43m x 0.43m x 0.043m were prepared from the different crushed quarry aggregates. The British Pendulum Number (BPN) and the Texture Depth (TD) were determined using the British portable skid tester and the sand patch methods, respectively. The regression analysis was performed to correlate the BPN with AN, SA, VMA and TD and to correlate VTM, TD and density with AN. The results of the regression showed that there is a correlation of skid resistance with AN, VMA, and also there is a correlation between TD and AN ( $R^2 = 0.67$ ).

Finally, Stepwise, Forward and Backward regression methods were performed, using statistical analysis software MINITAB. This was used to predict the relationship between skid resistance and the physical parameters of the aggregate and the performance characteristic of the mix, such as Angularity Number, Polished Stone Value, Particle Shape Index, Flakiness, Texture Depth, Voids in Total Mix and Voids in mineral aggregate. The best model with the highest regression coefficient  $R^2 = 0.87$  was selected, using the backward regression method. This model is highly recommended to predict a high friction wearing course.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk Ijazah Master Sains

**KESAN NOMBOR KESISIAN KE ATAS KEDALAMAN TEKSTUR DAN  
RINTANGAN GELINCIRAN STONE MASTIC ASPHALT**

Oleh

**MOHTADY ALI MUSA NORELDIEN**

**Mac 2002**

**Pengerusi : Professor Ir. Dr. Radin Umar Radin Sohadi**

**Fakulti : Kejuruteraan**

Kemalangan terbabas dan tergelincir akibat kurangnya daya cengkaman antara tayar dan permukaan jalan terutamanya pada permukaan turapan yang basah adalah merupakan antara masalah utama kepada pengguna jalan raya. Kajian ini memeriksa parameter utama yang boleh membantu menghasilkan geseran yang tinggi pada turapan bagi mengawal gelinciran. Dua parameter yang dikenalpasti adalah mikrotekstur dan makrotekstur batuan. Salah satu faktor yang mengawal parameter makrotekstur adalah bentuk batuan yang digunakan dalam kerja-kerja turapan.

Dalam kajian ini hanya batuan dengan kesisian kecil boleh dihasilkan dengan menggunakan Mesin Penghancur UPM. Namun begitu, segala usaha untuk menghasilkan ketetapan kesisian secara meluas tidak berjaya dilakukan. Daripada lapan puluh satu kuari yang dikaji didapati hanya lapan kuari sesuai bagi kajian ini. Ini adalah kerana sistem pemecahan batuan yang berbeza menghasilkan julat

kesisian yang tinggi. Batuan-batuan yang dikumpulkan diuji bagi Nombor Kesisian (AN) dan Indeks Bentuk (PI) di samping ujian sifat-sifat fizikal dan petrografi. Batuan-batuan tersebut kemudian dicampurkan dengan asfalt optimum bergred penusukan 60-70 mengikut kaedah campuran UPM di makmal.

Sejumlah seratus dua puluh sampel disediakan dan diuji bagi ketumpatan, modulus keanjalan dan analisis rongga. Selain itu, ujian Marshall dan pengaliran, ujian rayapan statik dan dinamik dan kekuatan modulus tegangan juga dijalankan. Analisis regresi digunakan bagi menghubungkan Nombor Kesisian dengan kestabilan, modulus keanjalan, ketumpatan, rongga dalam campuran, rongga dalam asfalt, kecekapan kembalian statik dan ujian luas permukaan dengan menggunakan perisian EXCEL. Hubungkait tersebut bergantung kepada pembolehubah regresi. Hasil daripada analisis regresi membuktikan memang terdapat hubungan yang bererti bagi Nombor Kesisian dengan ketumpatan, rongga dalam campuran, rongga dalam asfalt dan luas permukaan.

Sampel papak (0.43m x 0.43m x 0.043m) juga disediakan untuk ujian Nombor Pendulum British dan ujian kedalaman tekstur. Kajian ini dilakukan dengan menggunakan Penguji Rintangan Gelinciran Pendulum British dan kaedah tampalan pasir. Analisis regresi dijalankan bagi menghubungkan Rintangan Gelinciran dengan Nombor Kesisian, luas permukaan, rongga dalam mineral batuan dan kedalaman tekstur. Selain itu, analisa regresi ini juga mengaitkan Nombor Kesisian



dengan rongga dalam campuran, kedalaman tekstur dan ketumpatan. Hasil daripada analisis regresi menunjukkan terdapat hubungan antara rintangan gelinciran dengan Nombor Kesisian, rongga dalam mineral batuan dan terdapat hubungkait antara ujian Nombor Kesisian dan ujian kedalaman tekstur ( $R^2=0.67$ ).

Selain itu, analisis regresi kaedah kehadapan dan kebelakang telah dijalankan dengan menggunakan perisian MINITAB. Analisis statistik ini adalah untuk menjangka hubungan antara cengkaman dengan parameter fizikal bagi campuran. (Nombor Kesisian, rongga dalam campuran, Nilai Kelicinan Batuan, Indeks Bentuk, Keleperan, Kedalam Teksur, rongga dalam mineral batuan). Model terbaik dengan pembolehubah regresi ( $R^2 = 0.87$ ) dipilih hasil daripada ujian regresi kebelakang. Model ini adalah dicadangkan untuk menjangkakan lapisan haus bercengkaman tinggi.

## **ACKNOWLEDGEMENTS**

Thanks to almighty Allah who gave me power, strength, and patience to finish this Master program and Peace be upon his final Prophet and Messenger Mohammed Ibn Abdellah.

I would like to express my utmost thanks to my supervisor Professor Ir. Dr. Radin Umar Radin Sohadi for his supervision, guidance, patience and constructive criticism throughout this study. My sincere thanks go to Dr. Bujang B. Kim Huat, Mr. Salihudin Hassim, Mr. Ratnasamy Muniandy and Mr. Hussain Hamid for their valuable comments and constructive criticism.

My appreciation also goes to Dr. Suliman and Dr. Siti Zawyah for their help and advise during this study. My thanks also goes to the Geological Department and the Mines Department in Tabung Haji and the Quarry Managers.

I would also like to extend my thanks to the lab technician Tn. Haji Razali Mohd Amin and my colleague and my friends Dr. Omer Arabi, Dr. Izzeldin Babikir and Elwaleed Awad Khidir for their help and encouragement.

I wish to express my sincere gratitude to my brother-in-law Prof. Dr. Hassan El-Nager and my sister Samia for their support throughout the course of my study.

Last but not least, I extend my deepest gratitude and thanks to my mother, brothers and sisters for their support, patience and encouragement. Without their help and encouragement I would never have finished this valuable undertaking.

I certify that an Examination Committee met on 9<sup>th</sup> March 2002 to conduct the final examination of Mohtady Ali Musa Noreldien on his Master of Science thesis entitled “The Effects of Angularity Number on Texture Depths and Skid Resistance of Stone Mastic Asphalt” in accordance with Universiti Pertanian Malaysia (Higher Degree) Act 1980 and Universiti Pertanian Malaysia (Higher Degree) Regulations 1981. The Committee recommends that the candidate be awarded the relevant degree. Members of the Examination Committee are as follows:

**D.N. TRIKHA, Ph.D.**

Professor,  
Department of Civil Engineering  
Faculty of Engineering,  
Universiti Putra Malaysia  
(Chairman)

**RADIN UMAR RADIN SOHADI, Ph.D.**

Professor/ Dean  
Faculty of Engineering,  
Universiti Putra Malaysia  
(Member)

**BUJANG B.KIM HUAT, Ph.D.**

Department of Civil Engineering  
Faculty of Engineering,  
Universiti Putra Malaysia  
(Member)

**SALIHUDIN HASSIM, M. Sc.**

Department of Civil Engineering ,  
Faculty of Engineering,  
Universiti Putra Malaysia  
(Member)



**SHAMSHER MOHAMAD RAMADILI, Ph.D.**

Professor/ Deputy Dean  
School of Graduate Studies  
Universiti Putra Malaysia.

Date: 02 MAY 2002

This thesis submitted to the Senate of Universiti Putra Malaysia has been accepted as fulfilment of the requirement for the degree of Master of Science.



---

**AINI IDERIS, Ph.D.**  
Professor  
Dean, School of Graduate Studies  
Universiti Putra Malaysia.

Date: **13** JUN 2002

## DECLARATION

I hereby declare that the thesis is based on my original work except for quotations and citations, which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at UPM or other institutions.



**MOHTADY ALI MUSA**

Date: 02 MAY 2002

## TABLE OF CONTENTS

	<b>Page</b>
<b>DEDICATION</b>	<b>ii</b>
<b>ABSTRACT</b>	<b>iii</b>
<b>ABSTRAK</b>	<b>vi</b>
<b>ACKNOWLEDGEMENTS</b>	<b>ix</b>
<b>APPROVAL SHEETS</b>	<b>xi</b>
<b>DECLARATION FORM</b>	<b>xiii</b>
<b>LIST OF TABLES</b>	<b>xix</b>
<b>LIST OF FIGURES</b>	<b>xxii</b>
<b>LIST OF PLATES</b>	<b>xxiv</b>
<b>LIST OF ABBREVIATIONS</b>	<b>xxv</b>
 <b>CHAPTER</b>	
 <b>I INTRODUCTION</b>	 <b>1</b>
Background of Study	1
Tyre and Pavement Interaction Phenomena	4
Background of Stone Mastic Asphalt (SMA)	7
Background of Aggregate in Malaysia	8
Problem Statement	9
Objectives of the Study	10
Importance of the Study	11
Research Hypotheses	12
 <b>II LITERATURE REVIEW</b>	 <b>13</b>
Skidding Phenomena	13
Friction Phenomena and its Effect on Pavement Surface	14
Interaction between Tyre and Pavement	15
Road Surface Characteristics	15
Importance of Physical Characteristics and Types of Aggregate	17
Influence of Aggregate Characteristics on Pavement Surface	19
Coarse and Fine Aggregate Influences on Skid Resistance & T.D	20
Influence of Cubical and Flaky Aggregate on Pavement Surfaces	21
Angularity of Coarse Aggregate and Skid Resistance	23
Effect of Mineral Composition on Shape of Aggregate	26
Rock Crushing	27
Crushing Machinery Techniques	31
Impact Crushing	31
Attrition Techniques	33
Shear Crushing	34

Compression Mechanism	35
Characteristics Of Aggregate Gradations	36
Dense-graded	36
Open-graded Mix	37
Open-graded Mixtures and its Advantages	38
Filler	39
Optimization of Surface Texture Desirable	41
Microtexture	43
Macrotexture	43
Hydroplaning	45
Viscous Hydroplaning	45
Rubber (Tyre tread) Reversion Hydroplaning	46
Dynamic Hydroplaning	48
Influence of Vehicle Tyres on Skidding	50
Rocks	52
Rock Forming Minerals	53
Metallic Minerals	53
Major Constituents of Rocks	54
Silicates	54
Carbonates	55
Sulfates	56
Hardness of Rocks	56
Aggregate Mineralogy	57
Common Minerals Found in Aggregates	57
Effect of Mineralogy on Performance	58
Minerals and Skid Resistance of Aggregate	58
Worldwide Experience in HFWC Pavements	60
United State of America	60
France	62
Stone Mastic Asphalt in the European Countries	63
Malaysian UPM-Stone Mastic Asphalt	65
Design Principles of SMA	66
 <b>III</b>	
<b>MATERIALS AND METHODS</b>	68
High Friction Wearing Coarse Chart A	69
High Friction Wearing Coarse Chart B	70
Particle Shape and Surface Texture	72
Particle Index Test	72
Angularity Number Test	74
Preparation and Procedure of Angularity Test	75
Test Procedure and Calculations	76
Flat and Elongated Test	77
Ten Percent Fine Test	77
Aggregate Crushing Value	78



Impact Value	79
Specific Gravity	79
Absorption Test	80
Durability and Soundness Test	81
Surface Area	81
Laboratory Crushing Techniques	83
Site Selection and Data Collection	86
Asphalt Testing	88
Penetration	88
Softening Point	88
Flash and Fire point	89
Thin Film Oven Test	90
Determination of Asphalt Content	91
Marshal Method and Procedure	91
Stability Test	93
Percent Voids in Compacted Mineral Aggregates	93
Percent Air Voids in Compacted Mixture	94
Resilient Modulus Test	95
Test Procedure	95
Static Creep Test	96
Dynamic Creep Test	97
Moisture Induced Damage Test	98
Procedure	99
Portable Skid Resistance Tester	99
The Measurement of Texture Depth by the Sand Patch Method	100
Apparatus and Material	100
Test Procedure	101
Development of Prediction Model	102
Stepwise Procedure	103
Forward Selection Procedure	103
Back Elimination Procedure	105
<b>IV RESULTS AND DISCUSSION</b>	<b>106</b>
Conclusion on the Laboratory Crushing	110
Selection of Quarries	111
Malaysian Quarries Crushing System	112
Angularity Number	113
Statistical Analysis for AN	113
Particle Shape Index	115
Statistical Analysis for PI	115
Correlation between AN and PI	117
Surface Area of Crushed Aggregate for the Quarries	126
Comparison between the Polish Stone Value of the Quarries	129
Comparison between the Materials and the Physical Properties of	

	the Quarries	130
	Petrography of Rocks	131
	Jaksa Quarry	131
	Puchong Quarry	132
	Madu Jaya Quarry	133
	JKR Kuantan Quarry	134
	G.B. Quarry	135
	Asphalt Cement Physical Test	136
	Penetration Test	136
	Softening Point	137
	Flash and Fire Point	137
	Thin Film Oven Test	138
	Summary of the Asphalt Tests	139
	Optimum Asphalt Content	140
	The Stability and AN	141
	The Resilient Modulus and the AN	142
	Relationship between Density and AN	143
	Relationship between VTM and AN	145
	Relation between VMA and AN	147
	Moisture Susceptibility of the Marshall Samples of Quarries	149
	The Relation between Static Recovery Efficiency and AN	151
	The Relation between Surface Area and AN	153
	Dynamic Creep Modulus	155
	Relationship between Skid Resistance and Angularity Number	157
	VMA and BPN	159
	The Relationship between the Texture Depth and AN	159
	Texture Depth and BPN	161
	Model Building	162
	Regression Methods	162
	Statistical Analysis for the BPN	166
	Comparison between Model and Experimental Results	168
	Sensitivity Analysis of PSV and AN Values on BPN Model	169
	Influence of AN Values in BPN	170
	Comparison of Model with Previous Research Models	172
<b>V</b>	<b>CONCLUSION AND RECOMMENDATIONS</b>	<b>174</b>
	<b>REFERENCES</b>	<b>178</b>
	<b>APPENDICES</b>	<b>186</b>
<b>A</b>	Marshall Stability Test	186
<b>B</b>	Indirect Tensile Modulus Test	190
<b>C</b>	Static Load Asphalt Creep Test	194
<b>D</b>	Repeated Load Asphalt Creep Test	213
<b>E</b>	SPSS Data Output	229

F	Letters to/from the Quarries	242
G	Names of the Contacted Quarries	249
<b>VITA</b>		254

## LIST OF TABLES

Table	Page
1.1 Road Crash by Road Surface Condition	2
1.2 Percentage of Skidding Accidents	3
2.1 General Classification of Rocks	52
2.2 Common Rock Forming Mineral and Their Properties.	54
2.3 Hardness Scale	56
2.4 Constituents of the Commoner Rocks	57
3.1 Sizes used for Measuring Aggregate Angularity Number	75
3.2 Surface Area Factors	82
3.3 Calculation of Surface Area	83
4.1 Granite and Limestone Physical Properties After Crushing using UPM Portable Crushing Techniques	108
4.2 Angularity Number Test Data For Eight Quarries in Peninsular Malaysia	113
4.3 ANOVA for Angularity Number	114
4.4 Means of Angularity Number of Quarries	114
4.5 Particle Shape Index Test Data For Eight Quarries in Peninsular Malaysia	115
4.6 ANOVA for Particle Shape Index	116
4.7 Means of Particle Shape Index of the Quarries	116
4.8 Correlation Output of SPSS between AN and PI	117
4.9 Summary for Aggregate Test for the Whole Quarries	127

4.10	Summary for Aggregate Test For Negri Roadstone Quarry	128
4.11	Penetration Test for Asphalt	136
4.12	Softening Point Test for Asphalt	137
4.13	Flash & Fire Point Test for Asphalt	137
4.14	Thin Film Test for Asphalt	137
4.15	Summary for Asphalt Test	139
4.16	SMA-14 Gradations	140
4.17	Properties of SMA 14	141
4.18	Relationship between Stability and AN	142
4.19	Average Data of the AN and Resilient Modulus	143
4.20	Average Data of the AN and Density	144
4.21	Average data of AN and VTM	146
4.22	Average data of AN and the VMA	148
4.23	Data of the TSR of the Marshall Samples of the Quarries	150
4.24	Static Creep Test Data of the Quarries	152
4.25	Data about the Surface Area and the AN Average	154
4.26	Dynamic Creep Modulus Test for Each Quarry	155
4.27	Average Data of The BPN and AN	157
4.28	Data on the BPN and Voids in Mineral Aggregate	159
4.29	The Data of the AN and the Texture Depth of the Slabs using Sand Patch Method	160
4.30	The Quarries and the Average of Skidding and TD	161
4.31	Stepwise Regression Model of BPN on Seven Predictors	165

4.32	Regression Result of BPN Model	165
4.33	The Real and Calculated Model Values	170
4.34	Calculated Model Values for Different AN	173
5.1	Optimum Gradation for HFWC	176

## LIST OF FIGURES

Figure		Page
1.1	Relationship of Speed and Percentage of Skidding Accident	4
1.2	Production of Aggregates in Malaysia	8
1.3	Road Allocation and Expenditure for Five-year Development	9
2.1	Angular and Rounded Shapes of Aggregate	25
2.2	Mechanical Reduction by Impact	28
2.3	Mechanical Reduction through a Combination of Impact and Attrition in a Hammermill	33
2.4	Mechanical Reduction through a Combination of Shear, Impact, and Compression in a Single-roll Crusher	34
2.5	Mechanical Reduction by Compression and Impact in a Specially Designed Jaw Crusher Crushing without Rubbing	35
2.6	Aggregate Gradations	40
2.7	Influence of Road Surface Texture on Traffic Characteristics	42
2.8	Terms Used to Describe the Texture of a Road Surface	44
3.1a	Methodology Flow Chart (A)	69
3.1b	Methodology Flow Chart (B)	70
3.2	Data Collected from the Different States in Peninsular Malaysia	87
3.3	Static Creep Permanent Deformation Diagram	96
3.4	Dynamic Creep Sample inside MATTA Machine	97
3.5	View of Specimen at Moisture Induced Damage Test	98

4.1	Limestone Crushing Gradation	107
4.2	Granite Crushing Gradations	109
4.3	Malaysian Quarries Crushing Systems	112
4.4	Comparison between Angularity Number and Particle Shape Index	118
4.5	Madu Jaya Gradation	119
4.6	GB Quarry (Gyratory System) Gradation	120
4.7	Puchong Quarry (Gyratory System) Gradation	121
4.8	Jaksa Quarry (Alex Cone System) Gradation	122
4.9	Jaksa (Jaques Cone System) Gradation	123
4.10	JKR Kuantan Quarry (Cone System) Gradation	124
4.11	GB Quarry (Impact System) Gradation	125
4.12	Surface Area Comparison	126
4.13	Polished Stone Value of the Different Quarries	129
4.14	Comparison between Physical Properties of Stones with Different Quarries Crushing Systems	130
4.15	Relationship between AN and the Density of Samples	144
4.16	Relationship between AN and the Voids in Total Mix	146
4.17	Relationship between AN and the Voids in Mineral Aggregate	149
4.18	Relationship between AN and the Tensile Strength Ratio	151
4.19	Relationship between AN and the Static Recovery Efficiency	153
4.20	Relationship between the SA of Aggregate and AN	154



4.21	Strain vs Load Cycles	156
4.22	The Relationship between BPN and AN	158
4.23	The Relationship between AN and the Texture Depth	160
4.24	Comparison between Computed and Experimental Values	169
4.25	Influence of PSV and AN on BPN Model	170
4.26	Variations of AN on BPN	171